

Type	Tip	OG-03-100	OG-03-160	OG-03-200	OG-03-300	OG-03-400	OG-03-500	OG-03-600	OG-03-800	OG-03-1000	OG-03-1500	OG-03-2000	OG-03-2500	OG-03-3000	OG-03-4000	OG-03-5000	OG-03-6000	
Capacity	Kapasite	100	160	200	300	400	500	600	800	1000	1500	2000	2500	3000	4000	5000	6000	
Diameter (D)	Depo Çapı (D)	480	480	550	650	750	750	750	900	1000	1200	1350	1470	1470	1650	1650	1750	
Width (B)	Genişlik (B)	600	600	700	750	870	870	870	1100	1100	1350	1500	1620	1620	1820	1820	1920	
Height (H)	Yükseklik (H)	1160	1610	1420	1900	1825	1825	2025	2010	2015	1988,5	2040	2145	2600	3000	3000	3750	
Cold Water Inlet-Outlet (A)	Soğuk Su Giriş -Dönüş Bağlantısı (A)	1" / 235	1 1/4" / 235	1 1/4" / 235	1 1/4" / 235	1 1/4" / 240	1 1/4" / 240	1 1/4" / 240	1 1/2" / 300	1 1/2" / 300	1 1/2" / 350	1 1/2" / 350	2" / 370	2" / 350	3" / 800	3" / 800	3" / 850	
Hot Water Outlet-Inlet (W)	Sıcak Su Giriş -Dönüş Bağlantısı (W)	1" / 800	1 1/4" / 1380	1 1/4" / 1150	1 1/4" / 1640	1 1/4" / 1280	1 1/4" / 1580	1 1/4" / 1780	1 1/4" / 1700	1 1/4" / 1740	1 1/4" / 1680	1 1/4" / 1700	1 1/4" / 1700	2" / 2180	2" / 2250	3" / 2760	3" / 2990	
Circulation (S)	Sirkülasyon (S)	1" / 850	1 1/4" / 650	1 1/4" / 650	1 1/4" / 850	1 1/4" / 800	1 1/4" / 850	1 1/4" / 800	1 1/2" / 900	1 1/2" / 875	1 1/2" / 850	1 1/2" / 900	1 1/2" / 1150	2" / 1300	2" / 1400	3" / 1550	3" / 1750	
Thermostat (T1)	Termostat girişi (T1)	Ø 9 / 340	Ø 9 / 340	Ø 9 / 375	Ø 9 / 375	Ø 9 / 417	Ø 9 / 417	Ø 9 / 417	Ø 9 / 402	Ø 9 / 438	Ø 9 / 455	Ø 9 / 470	Ø 9 / 585	Ø 9 / 583	Ø 9 / 650	Ø 9 / 650	Ø 9 / 800	
Thermostat (T2)	Termostat girişi (T2) / Termostat Sensör girişi	Ø 9 /	Ø 9 / 1380	Ø 9 / 1145	Ø 9 / 1642	Ø 9 / 1207	Ø 9 / 1507	Ø 9 / 1707	Ø 9 / 1532	Ø 9 / 1658	Ø 9 / 1643	Ø 9 / 1644	Ø 9 / 1625	Ø 9 / 2023	Ø 9 / 2250	Ø 9 / 2780	Ø 9 / 3050	
Anode (N)	Anot (N)	1 1/4" / 1444	1 1/4" / 1594	1 1/4" / 1377	1 1/4" / 1877	1 1/4" / 1484	1 1/4" / 1784	1 1/4" / 1994	1 1/4" / 1980	1 1/4" / 1976	1 1/2" / 1900	1 1/2" / 1985	1 1/2" / 1980	1 1/2" / 1980	1 1/2" / 2450	1 1/2" / 2950	1 1/2" / 3435	1 1/2" / 3675
Electrical Heating Element (R)	Elektrikli Isıtıcı Girişi (R)	1 1/2" / 650	1 1/2" / 880	1 1/2" / 795	1 1/2" / 1191	1 1/2" / 885	1 1/2" / 1027	1 1/2" / 1132	1 1/2" / 1217	1 1/2" / 1280	1 1/2" / 1315	1 1/2" / 1313	1 1/2" / 1330	2" / 1743	2" / 1680	2" / 2050	2" / 2090	
Flange (Ø1) (M)	Flanş (Ø 1) (M)	DN 100 / 320	DN 100 / 320	DN 100 / 336	DN 100 / 336	DN 100 / 387	DN 100 / 387	DN 200 / 387	DN 200 / 477	DN 200 / 488	DN 200 / 717	DN 200 / 716	DN 200 / 755	DN 200 / 763	DN 200 / 1200	DN 400 / 1380	DN 400 / 1550	
Max. Boiler/Operation pressure	Boiler Max. Çalışma Basıncı	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	10 bar	
Max. Boiler/Test pressure	Boiler Test Çalışma Basıncı	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	13 bar	
Weight	Bütür Ağırlığı	50	65	80	100	125	130	160	200	250	400	480	655	750	1200	1580	1700	